

WYSE CLOUD CLIENT COMPUTING PRODUCT COMPARISON CHART

| WYSE DESKTOP THIN CLIENTS | Wyse ThinOS | | | | Thin Client Operating System | | | | | | | | | | | | | | | | | | | | | | | |
|--|-----------------------------------|-----------|-----------|-----------|------------------------------|-----------|-----------|-------|-----------|-------|--------|-------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|---------------|--------------------|-------|--------|----------------|--------------------|------|-------|
| | S10 | C10LE | V10LE | R10L | S30 | C30LE | V30LE | T50 | V50LE | C50LE | R50L | R50LE | C90LE | V90LE | R90L | R90LE | C90LEW | V90LEW | R90LW | R90LEW | Z90SW / Z90DL | C90LE7 | R90L7 | R90LE7 | Z90SW / Z90DL7 | | | |
| Major software features | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Citrix ICA, Citrix PNAgent, Microsoft RDP | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Citrix Web Interface: □ PNAgent-based, ■ Web-based | □ | □ | □ | □ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Citrix XenDesktop | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Wyse RDP (RDP7 Compatible) □, Microsoft RDC 7.0 ■ | □ | □ | □ | □ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Microsoft RDC 7.1 with RemoteFX | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| VMware View 4.x (RDP) | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| VMware View 4.x w/PCoIP | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Local application execution | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Local Multimedia capabilities (■ limited, ● good, □ best) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MS MediaPlayer support (□= optional local, ■ = included) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Browser (□ = server-based, ■ = basic, ● = full browser) | □ | □ | □ | □ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Java (□ = server-based, ■ = local) | □ | □ | □ | □ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Smart card authentication (□= broker, ■ = within session) | □ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| X Window X11R6 (□ = server-based, ■ = local) | □ | □ | □ | □ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Wyse TCX Suite 4.0 (all components including Flash Acceleration) (8) | | ■ | ■ | ■ | | | | | | | | | | | | | | | | | | | | | | | | |
| Wyse Virtual Desktop Accelerator support | | ■ | ■ | ■ | | | | | | | | | | | | | | | | | | | | | | | | |
| Terminal Emulation | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| System software security | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| □ = Secure ICA, ■ = "Read-only" data access, ● = Both | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |
| Third-party add-ons | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Administration and management | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Wyse Device Manager Agent and Workgroup License (7) | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Device image update method (□=Pull, ■=Push, ●=Both) | □ | □ | □ | □ | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |
| Auto-deploy via DHCP / FTP | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Wyse Configuration Manager | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Simple USB imaging solution with Wyse USB Firmware Tool | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Memory densities (Flash/RAM) as available as a custom (3) | 0/128 | 128F/512R | 128F/512R | 128F/512R | 128F/256R | 128F/512R | 128F/512R | 1G/1G | 128F/256R | 1G/1G | 1G/1G | 1G/1G | up to 4G/2G | up to 2G/1G | up to 4G/2G | up to 4G/2G | up to 4G/2G | up to 2G/1G | up to 4G/2G | up to 4G/2G | up to 4G/2G | 2G/2G up to 32G/4G | 4G/2G | 4G/2G | 4G/2G | 4G/2G up to 32G/4G | | |
| ■ = RAM is upgradeable ● = Both Flash and RAM are upgradeable | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Networking | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| PPP, 10/100Base-T Fast Ethernet ■, Gigabit Ethernet □, support for Fiber NIC (2) ● | ■ | □ | □ | □ | ■ | □ | □ | □ | ■ | □ | □ | □ | ■ | □ | □ | □ | ■ | □ | □ | □ | ■ | □ | □ | □ | ■ | □ | □ | □ |
| Wireless support (□ external, ◆ built-in opt.) | □ | ◆ | ◆ | ◆ | □ | ◆ | ◆ | ◆ | □ | ◆ | ◆ | ◆ | □ | ◆ | ◆ | ◆ | □ | ◆ | ◆ | ◆ | □ | ◆ | ◆ | ◆ | □ | ◆ | ◆ | ◆ |
| Internal 802.11 b/g factory option | | ✓ | ✓ | | | ✓ | | | | ✓ | | | | ✓ | | | | ✓ | | | | ✓ | | | | ✓ | | |
| Internal 802.11 b/g/n factory option | | | | ✓ | | ✓ | | | | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | | ✓ | ✓ | ✓ | | ✓ | | | | ✓ | ✓ | ✓ |
| Internal 802.11 a/b/g and dual band n (2.4GHz & 5GHz) factory option | | | | | | | | | | | | | | | | | | | | | | | | | | | | ✓ |
| External modem support (USB) | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| VNC for terminal shadowing (□ = Wyse Remote Shadow ■ = standard VNC) | □ | □ | □ | □ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| VPN (ThinOS supports PPTP only) | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. | Opt. |
| Chassis designs | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ● = Both horizontal and vertical stance, □ = vertical only | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● |
| Multi-display support (1) | | □ | □ | □ | | □ | □ | □ | | □ | □ | □ | | □ | □ | □ | | □ | □ | □ | | □ | □ | □ | | □ | □ | □ |
| Kensington lock slot | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Communications and I/O ports | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Serial port(s) | 1 | | 1 | 2 | 1 | | 1 | | 1 | | 2 | 2 | 1 | 2 | 2 | | 1 | 2 | 2 | 2 | 2 (2) | | | | 2 | 2 | 2 | 2 (2) |
| Parallel port | | | 1 | | | | 1 | | | | 1 | | | 1 | 1 | | | 1 | 1 | 1 | 1 (2) | | | | | | 1 | 1 (2) |
| Expansion slots (■ Cardbus/PCMCIA, ● PCIe) | | | | | | | ■ Opt. | | | | ■ Opt. | | | ■ Opt. | ● | | | ■ Opt. | ● | | | ● | | | | | ● | |
| USB 2.0 ports available (after keyboard and mouse) | 3 | 4 | 3 | 6 | 3 | 4 | 3 | 3 | 3 | 3 | 4 | 6 | 6 | 4 | 3 | 6 | 6 | 4 | 3 | 6 | 6 | 3 | 4 | 6 | 6 | 6 | 3 | 2 |
| SuperSpeed USB 3.0 ports | | | | | | | | | | | | | | | | | | | | | | | | | | | | 2 |
| PS/2 ports | | 2 | 2 | 2 | | 2 | 2 | | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 1 (2) | 2 | 2 | 2 | 1 (2) |
| Video output: ■ = VGA DB-15, ● = DVI-D, □ = DVI-I (4), ◆ = DisplayPort | ■ | □ | □ | ● | ■ | □ | □ | □ | □ | □ | ● | ● | □ | □ | ● | ● | □ | □ | ● | ● | □ | □ | ● | ● | □ | □ | ● | ◆ |
| Local printer support | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Hard drive (6) (■ = support for external option) | | | | ■ | | | | | | | | | | | | | | | | | | | | | | | | |
| Flash drive (6) (■ = support for external option) | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| CD-ROM/DVD drive (6) (■ = support for external option) | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Smart card reader (□ = internal (2), ■ = external option) | ■ | ■ | ■ | □ | ■ | ■ | ■ | □ | ■ | ■ | ■ | □ | ■ | ■ | ■ | □ | ■ | ■ | ■ | □ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Touchscreen support * (■ = standard) | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Audio output (analog) ■, Digital audio □ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Average Power consumption | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Less than 7 Watts ■, less than 15 Watts □ | ■ | ■ | □ | □ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ | ■ |
| Warranty | 3 years limited hardware warranty | | | | | | | | | | | | | | | | | | | | | | | | | | | |

* Wyse products work with a number of third-party vendor devices.

** Coming soon

- (1) May require optional monitor splitter cable sold separately
- (2) Factory-installed option
- (3) Factory-installed memory configuration subject to change
- (4) C, V, R, T and Z class models ship with a DVI-I to VGA (DB-15) adapter

- (5) Support for USB Virtualizer version 1.5.8 only
 - (6) External drives connect via USB
 - (7) Wyse Device Manager Enterprise available for better scalability and additional features
 - (8) Subject to licensing fees - please refer to Wyse TCX Suite documentation for more details
- UbuntuTM is a registered trade mark of Canonical Group Limited.

WYSE CLOUD CLIENT COMPUTING PRODUCT COMPARISON CHART

WYSE ZERO CLIENTS

FEATURE COMPARISON

| | Wyse Xenith | Wyse Xenith Pro | Wyse E01 | Wyse P20 |
|---|--|--------------------|--|--|
| Target Datacenter / Server | Citrix XenDesktop and Citrix XenApp* | | Microsoft Windows MultiPoint Server 2010 and 2011 | VMware View |
| Technology support | Rich Citrix HDX Experience | | Windows-based shared computing | Rich user experience with PCoIP hardware implementation |
| Virtual Desktop Operating System | | | | |
| Windows XP | ● | | | ● |
| Windows Vista | ● | | | ● |
| Windows 7 | ● | | ● | ● |
| End-User Application Use | <p>Built for Citrix XenDesktop and XenApp*, Wyse Xenith is where 'zero' really adds up: delivering the Citrix HDX experience with zero delays, zero management, zero security risks, (almost) zero energy use. Leaving nothing to stop this instant-on, plug-n-play, virus immune and high performance zero client from transforming the way you deploy intelligent desktops right across your enterprise or organization.</p> <p>Wyse Xenith pro adds:</p> <ul style="list-style-type: none"> - Twice the Citrix HDX performance – for truly dazzling multimedia, HD Flash content and unified communications. - Support for users needing dual digital displays including L-shaped configurations. - Class-leading connectivity: with 6 USB and 2 serial ports for excellent up to date and legacy peripheral support | | Wyse E01 Zero Clients have been specifically designed to work with Windows MultiPoint Server 2010 in order to provide a full rich Windows 7 desktop to students and maximum flexibility to teachers and administrators. They offer a truly low cost alternative for PC sharing technology through an innovative hardware design. | For virtual desktop or blade PC environments, the Wyse P class delivers workstation class performance for advanced applications including CAD, 3D solids modeling, video editing and advanced worker level office productivity. Based on a hardware PCoIP® engine, this stateless zero client requires no local operating system. Unlike more flexible software-based implementations, this dedicated hardware PCoIP engine delivers the highest level of display performance available. |
| Ideal for: | | | | |
| Call centers (Cross Industry) | ● | | | |
| CAD/CAM (Cross Industry) | | ● | | ● |
| Education | ● | | ● | ● |
| Finance | ● | ● | | ● |
| Government | ● | ● | | ● |
| Health Care | ● | ● | | ● |
| Manufacturing | ● | ● | | ● |
| Transport | ● | | | ● |
| All others | ● | | | ● |
| Chassis designs Both horizontal and vertical stance ●, vertical only □, horizontal only ■ | ● | | ■ | □ |
| Multi-display support (2 monitors) | ■ (1) | ■ | | ■ |
| Kensington lock slot | ■ | ■ | | |
| Networking | | | | |
| 10/100Base-T Fast Ethernet ■, Gigabit Ethernet □ | □ | | via USB 2.0 | □ |
| 802.11 b/g/n Wireless (factory option) | ● | | | |
| Communications and I/O ports | | | | |
| USB ports available (after keyboard and mouse) | 4 | 6 | 2 | 3 |
| Serial port(s) | | 2 | | |
| PS/2 ports | 2 | 2 | | |
| Video output (■ = VGA DB-15, ● = DVI-D, □ = DVI-I) | □ (3) | ● □ | ■ | 2 x □ |
| Average Power consumption | Less than 7 watts | Less than 14 watts | Less than 3 watts | Less than 16 watts |
| Warranty | 3 years limited hardware warranty | | 3 years limited hardware warranty | 3 years limited hardware warranty |

*Wyse Xenith supports Citrix XenApp Published Desktops.
(1) Requires optional monitor splitter cable sold separately

(3) ships with a DVI-I to VGA (DB-15) adapter

Last update August 9, 2011

WYSE CLOUD CLIENT COMPUTING PRODUCT COMPARISON CHART

WYSE CLOUD PCs FEATURE COMPARISON

| | Wyse C00LE | Wyse V00LE | Wyse R00L | Wyse Z00D | Wyse X00c |
|---|--|--|---|---|---|
| Desktop Operating System | | | | | |
| Windows XP | ● | ● | ● | ● | ● |
| Windows Vista | | | ● | ● | ● |
| Windows 7 | | | ● | ● | ● |
| End-User Application Use | Windows XP, Microsoft Office, Internet based curriculum, including basic multimedia (Flash, Quicktime) support | Windows XP, Microsoft Office, Internet based curriculum, including basic multimedia (Flash, Quicktime) support | Rich Windows 7 Aero experience, outstanding multimedia and 3-D CAD/CAM support. | Rich Windows 7 Aero experience, outstanding multimedia and 3-D CAD/CAM support. | Rich Windows 7 and multimedia experience for mobile users |
| Ideal for: | | | | | |
| Call centers (Cross Industry) | ● | ● | | | |
| CAD/CAM (Cross Industry) | | | ● | ● | |
| Education | ● | ● | ● | ● | ● |
| Finance | ● | ● | ● | ● | ● |
| Government | ● | ● | ● | ● | ● |
| Health Care | ● | ● | ● | ● | ● |
| Chassis designs Both horizontal and vertical stance ●, vertical only □, horizontal only ■ | ● | ● | ● | ● | 11.6" widescreen, laptop form factor |
| Multi-display support (2 monitors) | ■ (1) | ■ (1) | ■ | ■ | |
| Kensington lock slot | ■ | ■ | ■ | ■ | ■ |
| Memory densities (Flash/RAM) | 0 / 1GB or 0 / 2GB | 0 / 1GB | 0 / 1GB or 0 / 2GB | 0 / 2GB, up to 4GB RAM | 160GB HDD / 2GB RAM |
| Networking Fast Ethernet ■, Gigabit Ethernet □ | □ | ■ | □ | □ | ■ |
| Integrated wireless | | | | | 802.11b/g/n |
| Communications and I/O ports | | | | | |
| USB 2.0 ports available (after keyboard and mouse) | 4 | 3 | 6 | 3 | 3 |
| SuperSpeed USB 3.0 ports | | | | 2 | |
| Serial port(s) | | 1 | 2 | 2 (3) | |
| Parallel port(s) | | | | 1 (3) | |
| PS/2 ports | 2 | 2 | 2 | 1 (3) | |
| Video output (■ = VGA DB-15, ● = DVI-D, □ = DVI-I (4), ◆ = DisplayPort) | □ ² | □ ² | ● □ | □ ◆ | ■ |
| Media card reader | | | | | ■ |
| 1.3M pixel camera | | | | | ■ |
| Internal stereo speakers | | | | | ■ |
| Warranty | 3 years limited hardware warranty | 3 years limited hardware warranty | 3 years limited hardware warranty | 3 years limited hardware warranty | One-year limited warranty, 6 months battery warranty |

(1) Requires optional monitor splitter cable sold separately

(2) ships with a DVI-I to VGA (DB-15) adapter

(3) Factory-installed option

(4) C, V, R and Z class models ship with a DVI-I to VGA (DB-15) adapter

Last update March 28, 2011

WYSE CLOUD CLIENT COMPUTING PRODUCT COMPARISON CHART

| WYSE MOBILE THIN CLIENTS FEATURE COMPARISON | Wyse SUSE Linux Enterprise | Windows Embedded Standard 2009 | | Windows Embedded Standard 7 | |
|---|--|------------------------------------|-------------------------------------|-----------------------------|-------------------------------------|
| | X50c | X90cw | X90mw | X90c7 | X90m7 |
| Major software features | | | | | |
| Citrix ICA, Citrix PNagent, Microsoft RDP | ■ | ■ | ■ | ■ | ■ |
| Citrix Web Interface: □ PNAgent-based, ■ Web-based | □ ■ | □ ■ | □ ■ | □ ■ | □ ■ |
| Citrix XenDesktop | ■ | ■ | ■ | ■ | ■ |
| □ Wyse RDP (RDP7 Compatible), ■ Microsoft RDC 7.0 | □ | ■ | ■ | | |
| Microsoft RDC 7.1 with RemoteFX | | | | ■ | ■ |
| VMware View 4.x (RDP) | ■ | ■ | ■ | ■ | ■ |
| VMware View 4.x w/PCoIP | ■ | ■ | ■ | ■ | ■ |
| Local application execution | ■ | ■ | ■ | ■ | ■ |
| Local Multimedia capabilities (■ limited, ● good, □ best) | ● | ● | □ | ● | □ |
| MS Media Player support (■ = included) | | ■ | ■ | ■ | ■ |
| Browser (● = local with plug-ins) | ● | ● | ● | ● | ● |
| Java (■ = local) | ■ | ■ | ■ | ■ | ■ |
| Smart card authentication (□ = broker, ■ = within session) | □ ■ | □ ■ | □ ■ | □ ■ | □ ■ |
| X Window X11R6 (□ = server-based, ■ = local) | ■ | □ | □ | □ | □ |
| Wyse TCX Suite 4.0 (all components including Flash Acceleration) (1) | ■ | ■ | ■ | ■ | ■ |
| Wyse Virtual Desktop Accelerator support | ■ | ■ | ■ | ■ | ■ |
| Terminal Emulation | ■ | ■ | ■ | ■ | ■ |
| System software security | | | | | |
| □ = Secure ICA, ■ = "Read-only" data access, ● = Both | ● | ● | ● | ● | ● |
| Third-party add-ons | ■ | ■ | ■ | ■ | ■ |
| Administration and management | | | | | |
| Wyse Device Manager Agent and Workgroup License (6) | ■ | ■ | ■ | ■ | ■ |
| Device image update method (□ = Pull, ■ = Push, ● = Both) | ● | ■ | ■ | ■ | ■ |
| Auto-deploy via DHCP / FTP | ■ | ■ | ■ | ■ | ■ |
| Wyse Configuration Manager | | ** | ** | ■ | ■ |
| Simple USB imaging solution with Wyse USB Firmware Tool | ■ | | | ■ | ■ |
| Memory Configuration (3) | 1G/1G | 2G/1G up to 4GB Flash / 2GB RAM | 2G/2G Up to 32GB Flash / 4GB RAM | 4G/2G | 4G/2G Up to 32GB Flash / 4GB RAM |
| Laptop form factor (widescreen WXGA) | 11.6" | 11.6" | 14" | 11.6" | 14" |
| Display | 1366x768 | 1366x768 | 1366x768 | 1366x768 | 1366x768 |
| Multi-display support (□ = 2 monitors) | | | □ | | □ |
| Standard Battery | 6 cell. | 6 cell. | 6 cell. | 6 cell. | 6 cell. |
| Kensington lock slot | ■ | ■ | ■ | ■ | ■ |
| Networking | | | | | |
| PPP, 10/100Base-T Fast Ethernet ■, Gigabit Ethernet □ | ■ | ■ | □ | ■ | □ |
| Integrated wireless | ■ | ■ | ■ | ■ | ■ |
| Internal 802.11 b/g/n factory option | ✓ | ✓ | ✓ | | |
| Internal 802.11 a/b/g and dual band n (2.4GHz & 5GHz) factory option | | | | ✓ | ✓ |
| 3G capable, support for external option ■, internal option □ (4) | □ ■ | □ ■ | □ ■ | □ ■ | □ ■ |
| External modem support (USB) | ■ | ■ | ■ | ■ | ■ |
| VNC for terminal shadowing (□ = Wyse Remote Shadow ■ = standard VNC) | ■ | ■ | ■ | ■ | ■ |
| VPN | Opt. | Opt. | Opt. | Opt. | Opt. |
| Communications and I/O ports | | | | | |
| ExpressCard expansion slots (5) | | | ■ | | ■ |
| USB 2.0 ports | 3 | 3 | 1 | 3 | 1 |
| SuperSpeed USB 3.0 ports | | | 2 | | 2 |
| Video output (■ = VGA DB-15, ◆ = DisplayPort) | ■ | ■ | ■ ◆ | ■ | ■ ◆ |
| Local printer support | ■ | ■ | ■ | ■ | ■ |
| Hard drive (■ = support for external option) | ■ | ■ | ■ | ■ | ■ |
| Flash drive (■ = support for external option) | ■ | ■ | ■ | ■ | ■ |
| CD-ROM/DVD drive (■ = support for external option) | ■ | ■ | ■ | ■ | ■ |
| Smart card reader (□ = internal, ■ = support for external option) | ■ | ■ | □ opt. ■ | ■ | □ opt. ■ |
| Bluetooth support | ■ opt. | ■ opt. | ■ opt. | ■ opt. | ■ opt. |
| Media card reader | ■ | ■ | ■ | ■ | ■ |
| 1.3M pixel camera | ■ | ■ | ■ | ■ | ■ |
| Audio output (analog) ■, Digital audio □ | ■ | ■ | ■ □ | ■ | ■ □ |
| Internal stereo speakers | ■ | ■ | ■ | ■ | ■ |
| High Definition Audio | ■ | ■ | ■ | ■ | ■ |
| Warranty | One-year limited warranty, 6 months battery warranty | | | | |

* Wyse products work with a number of third-party vendor devices.

** Coming soon

(1) Subject to licensing fees - please refer to Wyse TCX Suite documentation for more details

(2) Clone mode only

(3) Factory-installed memory configuration subject to change

(4) Requires broadband access cards from wireless network providers

(5) Accepts 34mm & 54mm ExpressCards

(6) Wyse Device Manager Enterprise available for better scalability and additional features

Last update August 9, 2011



Wyse Technology Inc.
3471 North First Street
San Jose, CA 95134-1801

Sales:
(408) 473 1200

Wyse Sales
(800) GET WYSE
(800 438 9973)

Visit our website at:
www.wyse.com

Send email to:
sales@wyse.com

Wyse Customer Service Center:
(800) 800 WYSE
(800 800 9973)